

Easy UPS 3L 250kVA 400V 3:3 UPS, Startup 5x8

E3LUPS250KHS

Overview

Presentation	Easy-to-configure, easy-to-use and easy-to-service 250 kVA 3 phase UPS with an exceptional combination of competitive specifications, compact footprint, and highly available parallel and redundant designs. The EcoStruxure connected Schneider Electric Easy UPS 3L is the easy choice for business continuity on your shop floor or in your electrical room. Includes 5x8 start-up service.
Lead time	Special Order - Call for Quoted Lead Times

Main

Mani		
Main Input Voltage	400 V 3 phases	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	380 V 415 V	
Main Output Voltage	400 V 3 phases	
Other Output Voltage	380 V 415 V	
Rated power in W	250 kW	
rated power in VA	250 kVA	
Provided equipment	Dust filter Installation manual Start-up service	
Range of product	Easy UPS 3L	

Batteries & Runtime

Efficiency	View Efficiency Graph ☐	
Battery type	External battery system	
Battery voltage	+/- 216+/- 300 V	
Maximum short-circuit current	35 kA	
Discharge battery voltage	+/- 172.8+/- 240 V	

Physical

Colour	White (RAL 9003)	
Height	197 cm	
Width	60 cm	
Depth	85 cm	
Net weight	425 kg	
USB compatible	Yes	

Input

Maximum input current	451 A	
Max short time withstand current	35 kA	
Input harmonic distortion	Less than 3 % for full load	
Load power factor	0.5 leading to 0.5 lagging without derating	
Input voltage limits	323477 V	
Network frequency	4070 Hz	

Output

Maximum configurable power in VA	250 kVA	
Maximum configurable power in W	250 kW	
Output frequency	50 Hz sync to mains 60 Hz sync to mains	
Output harmonic distortion	< 2% linear load and < 4% non-linear load	
Output overload operation	10 minutes at 125% and 60 seconds at 150%	
UPS type	Double conversion online	

Conformance

Product certifications	CE EAC
	RCM

Environmental

Ambient air temperature for operation	030 °C	
Relative humidity	095 % non-condensing	
Operating altitude	04921 ft	
Ambient air temperature for storage	-2555 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	014999.8 m	
Acoustic level	70 dB	
Heat dissipation	49488 Btu/h	
IP degree of protection	IP20	

Communications & Management

Control panel	Touch screen LCD user interface
---------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2117 mm
Package 1 Width	1000 mm
Package 1 Length	800 mm
Package 1 Weight	470 kg

Contractual warranty

Warranty

1 year on-site repair or replace with factory authorized Start-Up



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint		
Total lifecycle Carbon footprint	325623	

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant with Exemptions	
SCIP Number	409c68a1-39a6-4e5f-b080-12befe783ad8	

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins


Product datasheet E3LUPS250KHS

Image of product / Alternate images

Alternative

18 Aug 2025

E3LUPS250KHS





E3LUPS250KHS

