

Easy UPS 3M 80kVA 400V 3:3 UPS for external batteries, Start-up 5x8

E3MUPS80KHS

Overview

Presentation	Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 80 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. It is supplied without batteries, so you can easily customize your battery solution. Includes 5x8 start-up service.
Lead time	Usually Ships within 6 Weeks

Main

Main Input Voltage	400 V 3 phases	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	380 V 415 V	
Main Output Voltage	400 V 3 phases	
Other Output Voltage	380 V 415 V	
Rated power in W	80 kW	
rated power in VA	80 kVA	
Provided equipment	Dust filter Installation guide Start-up service	
Range of product	Easy UPS 3M	

Batteries & Runtime

Efficiency	View Efficiency Graph ☐	
Battery type	External battery system	
Number of battery filled slots	0	
Number of battery free slots	0	

Physical

Colour	White (RAL 9003)	
Height	91.5 cm	
Width	36 cm	
Depth	85 cm	
Net weight	140 kg	
USB compatible	Yes	

Input

•	
Maximum input current	146 A
Max short time withstand current	10 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	0.99
Input voltage limits	342477 V
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Network frequency	4070 Hz

Output

•		
Maximum configurable power in VA	80 kVA	
Maximum configurable power in W	80 kW	
Output frequency	50 Hz sync to mains 60 Hz sync to mains	
Harmonic distortion	Less than 3 %	
Output harmonic distortion	< 3% linear load and < 5% non-linear load	
Output overload operation	10 minutes at 125% and 60 seconds at 150%	
UPS type	Double conversion online	
Wave type	Sine wave	
Bypass type	Built-in static bypass	
Crest factor	3:1	

Environmental

Ambient air temperature for operation	040 °C	
Relative humidity	095 % non-condensing	
Operating altitude	04921 ft	
Ambient air temperature for storage	-2555 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	015240 m	
Acoustic level	65 dBA	
Heat dissipation	14659 Btu/h	
IP degree of protection	IP20	

Communications & Management

Free slots	1	
Control panel	Touch screen LCD user interface	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	114.000 cm

Package 1 Width	47.500 cm
Package 1 Length	96.500 cm
Package 1 Weight	164.000 kg

Contractual warranty

Warranty

1 year on-site repair or replace with factory authorized Start-Up



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	102744
Environmental Disclosure	Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Bcc48c21-81f4-41e7-bf2b-336ef659ee43

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



