

Product datasheet

Specifications



APC Back-UPS Pro, 1000VA/
600W, Tower, 230V, 6x India 6A
outlets, AVR, LCD, User
Replaceable Battery

BR1000G-IN

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	600 W
rated power in VA	1000 VA
Product or component type	Uninterruptible power supply (UPS)
output connection type	4 India 3-pin 6A 2 India 3-pin 6A surge
Cable length	1.5 m
Number of cables	1
Battery type	Lead-acid battery
Range of product	Back-UPS Pro

Batteries & Runtime

Run Time	View Runtime Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	7.4 h
Number of battery replacement quantity	1
Battery charger power	29 W rated
Battery life	2...4 year(s)
Replacement battery	APCRBC124 APCRBC144
Extended runtime	1

General

Provided equipment	telephone cable user manual USB cable warranty card
Number of power module free slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	30.1 cm
Width	11.4 cm
Depth	38.2 cm
Net weight	11.35 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	India 3-pin 6A
Input voltage limits	170...294 V

Output

Maximum configurable power in W	600 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Efficiency	84 % (full load) 80 % (half load)
Maximum configurable power in VA	1000 VA
Transfer time	8 ms typical : 12 ms maximum

Conformance

Product certifications	BIS
------------------------	-----

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15240 m
Acoustic level	45 dBA

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	680 J
Let through voltage rating	330 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.1 cm
Package 1 Width	48.3 cm
Package 1 Length	22.9 cm
Package 1 Weight	12.77 kg
SCC14	20731304286244

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	Yes