Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

APC



APC Smart-UPS XL 2200VA 230V No Battery

SUA2200UXI

Overview

Lead time Usually in Stock

Main

Product or component type Uninterruptible power supply (UPS)

Complementary

Communication port type SmartSlot

Batteries & Runtime

Run Time	View Runtime Graph ☐
Battery type	External battery system
Additional information	Unit ships without batteriessee UXI brochure for recharge times. Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	RBC55 [7]

General

Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Extended run
Redundant	No

Physical

Number of cables	1
Colour	Beige

Height	43.2 cm
Width	19.6 cm
Depth	54.4 cm
Net weight	28.64 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Main Input Voltage	230 V
Input Connection Type	IEC 320 C20
Input voltage limits	151302 V adjustable 160286 V
Network frequency	50/60 Hz +/- 5 Hz auto-sensing

Output

Main Output Voltage	230 V
Rated power in W	1980 W
rated power in VA	2200 VA
output connection type	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
Transfer time	2 ms typical
UPS type	Line interactive
Wave type	Sine wave
Output frequency	4753 Hz for 50 Hz nominal sync to mains 5763 Hz for 60 Hz nominal sync to mains

Conformance

Product certifications	C-Tick CE GOST VDE
	VDE

Environmental

Acoustic level	53 dBA
Heat dissipation	305 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	015240 m

Relative humidity	095 %	
Storage Relative Humidity	0 95 %	

Communications & Management

Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Emergency power off	Optional
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping response time: meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	55.9 cm
Package 1 Width	76.2 cm
Package 1 Length	38.1 cm
Package 1 Weight	33.64 kg

Contractual warranty

17 Aug 2025

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Energy Efficiency Optimized	Energy efficient product

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Product datasheet

SUA2200UXI

Image of product / Alternate images

Alternative





