Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

APC



APC Easy UPS BVX 2200VA, 230V, AVR, India Sockets

BVX2200LI-IN

Overview

Lead time	Usually in Stock

Main

wain		
Main Input Voltage	230 V	
Main Output Voltage	230 V	
Other Output Voltage	230 V	
Rated power in W	1200 W	
rated power in VA	2200 VA	
Product or component type	Uninterruptible power supply (UPS)	
output connection type	5 India 3-pin 6A	
Cable length	1.2 m	
Number of cables	1	
Battery type	Lead-acid battery	
Provided equipment	User manual	
Range of product	Easy UPS	

Batteries & Runtime

Run Time	View Runtime Graph ☐	
Efficiency	View Efficiency Graph ☐	
Number of battery filled slots	0	
Number of battery free slots	0	
Battery recharge time	6 h	
Battery voltage	24 V	
Battery capacity	9 Ah	
Extended runtime	0	
Replacement battery	APCRBC177 ☐	

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

UPS size WS

Physical

•		
Colour	Black	
Height	19.0 cm	
Width	14.0 cm	
Depth	39.0 cm	
Net weight	12.2 kg	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	
Two post mountable	0	
USB compatible	No	

Input

•	•	
Network frequency	4070 Hz +/- 5 Hz auto-sensing	
Plug standard	India 3-pin 16A	
Input voltage limits	140300 V	
Input protection type	Circuit breaker	

Output

Maximum configurable power in W	1200 W	
Output frequency	50/60 Hz +/- 1 Hz unsynchronised	
UPS type	Line interactive	
Wave type	Stepped approximation to a sinewave	
Graph display	1	
Maximum configurable power in VA	2200 VA	
Transfer time	6 ms typical : 10 ms maximum	

Conformance

Product certifications BIS

Environmental

Ambient air temperature for operation	040 °C	
Relative humidity	095 % non-condensing	
Operating altitude	03000 m	
Ambient air temperature for storage	-2050 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	015000 m	
Acoustic level	40 dBA	
IP degree of protection	IP20	

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone

Surge Protection and Filtering

Surge energy rate 255 J

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	49.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.2 kg

Contractual warranty

Warranty 2 Years on UPS & 1 Year on Battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	Ef3b165e-8e1d-4ef1-89c3-03b78b282225
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No

Image of product / Alternate images

Alternative



