

Product datasheet

Specifications



APC Smart-UPS 750VA USB & Serial 230V, India Specific

SUA750I-IND

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	Uninterruptible power supply (UPS)
---------------------------	------------------------------------

Complementary

Communication port type	SmartSlot
-------------------------	-----------

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery type	Lead-acid battery
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Number of battery replacement quantity	1

General

Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Height	15.7 cm
Width	13.7 cm
Depth	36.1 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	13.15 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Main Input Voltage	230 V
Input Connection Type	IEC 60320 C14
Input voltage limits	151...302 V adjustable 160...282 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Main Output Voltage	230 V
Rated power in W	500 W
rated power in VA	750 VA
output connection type	4 India 3-pin 6A
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	750 VA
Maximum configurable power in W	500 W
Transfer time	2 ms typical
UPS type	Line interactive
Wave type	Sine wave
Output frequency	47...53 Hz for 50 Hz nominal sync to mains

Conformance

Product certifications	BIS
------------------------	-----

Environmental

Acoustic level	41 dBA
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29 cm
Package 1 Width	50 cm
Package 1 Length	27 cm
Package 1 Weight	14.55 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative

